


Applied Meteorology Unit (AMU) Quarterly Report



31 January 2011

First Quarter FY-11

Contract NNK06MA70C



In this issue:

**Peak Wind Tool for User
LCC, Phase IV**

**Situational Lightning Clima-
tologies for Central Florida,
Phase V**

**Vandenberg AFB North Base
Wind Study**

**Upgrade Summer Severe
Weather Tool in MIDDs**

Launch Support

Dr. Watson supported the
Delta 4-Heavy launch on 21
November

Ms. Wilson and Mr. Wheeler
supported the Falcon 9
launch on 8 December

Falcon 9 launch photo by SpaceX/Chris Thompson
(<http://spaceflightnow.com/falcon9/002/remotes/>)

The AMU Team began four new tasks in this quarter:

- Ms. Crawford began work to improve the AMU-developed tool that provides the launch weather officers information on peak wind speeds that helps them assess their launch commit criteria;
- Dr. Bauman began updating lightning climatologies for airfields around central Florida. These climatologies help National Weather Service and Air Force forecasters determine the probability of lightning occurrence at these sites;
- Mr. Wheeler began a study for the 30th Weather Squadron at Vandenberg Air Force Base in California to determine if precursors can be found in weather observations to help the forecasters determine when they will get strong wind gusts in their northern towers; and
- Dr. Watson began work to update the AMU-developed severe weather tool with more data and possibly improve its performance using a new statistical technique.



1980 N. Atlantic Ave., Suite 830
Cocoa Beach, FL 32931
(321) 783-9735, (321) 853-8203 (AMU)


Quarterly Task Summaries

This section contains summaries of the AMU activities for the first quarter of Fiscal Year 2011 (October - December 2010). The accomplishments on each task are described in more detail in the body of the report starting on the page number next to the task name.

Peak Wind Tool for User LCC, Phase IV (Page 4)

Purpose: Recalculate the Phase III cool season peak wind statistics using stability as an added stratification. Although peak winds are an important forecast element for launch vehicles, the 45th Weather Squadron (45 WS) and Spaceflight Meteorology Group (SMG) indicate that they are a challenging to forecast. The Phase III tool helped alleviate this forecast difficulty. Stability has long been known to have a strong affect on surface wind speeds. Recalculating the statistics after stratifying by stability will make them more robust and useful to operations.

Accomplished: The wind tower and sounding data needed for this task were provided by Computer Sciences Raytheon (CSR). These data were quality-checked (QC'd) and processed for analysis. The Richardson number will be used to determine the stability stratification, which is calculated using virtual potential temperature and u/v wind components. The wind tower data were formatted to begin calculating these values for each level on each tower.



Situational Lightning Climatologies for Central Florida, Phase V (Page 5)

Purpose: Update the existing lightning climatology to improve operational weather support to Kennedy Space Center (KSC), Cape Canaveral Air Force Station (CCAFS), Patrick Air Force Base (PAFB), and commercial and general aviation across central Florida. The update includes adding more years of data to the database, adding more sites and adding stratifications for moisture and stability parameters. These updates will provide climatologies for new sites for which the 45 WS and National Weather Service have forecast responsibility, and to help forecasters distinguish lightning days that are more active from those that are less active within the same flow regime.

Accomplished: Received National Lightning Detection Network (NLDN) data (May-September 1989-2010) from the 14 WS and downloaded NWS sounding data from the NOAA Earth System Research Laboratory. Updated and tested S-PLUS scripts to create the warm season 2010 flow regime files and merged the flow regime data with the NLDN data. Generated lightning climatologies for all sites. Updated and delivered the graphical user interface (GUI) to the customers. Began incorporating the precipitable water observations from soundings at CCAFS, Jacksonville, Tampa and Miami into the sounding database.

Quarterly Task Summaries (continued)



Delta II at VAFB
Photo by Thom Baur/Boeing

Vandenberg Air Force Base North Base Wind Study (Page 7)

Purpose: Analyze local wind tower, surface, upper air and sounding data from Vandenberg Air Force Base (VAFB) to find precursors to high wind events in the north base towers. The 30 Weather Squadron (30 WS) states that terrain influences the unpredicted strong northeast winds that have been measured on several of the north base wind towers and exceed their 35 kt warning criteria. This study will look into those influences and document any precursors that may be found that will assist forecasters in analyzing their wind warning criteria.

Accomplished: VAFB data for the years 2004 to April 2010 to include wind towers and soundings were requested from the 30 WS in September 2010. Due to 30 WS workload issues, the tower data were not received until mid-October. Excel scripts were developed to decode the raw tower data. Once decoded, the data were input to Excel spreadsheets. The other data sets required for the task, upper air and surface maps along with VAFB sounding data were retrieved from other data archives.

Upgrade Summer Severe Weather Tool Phase III (Page 8)

Purpose: Upgrade the Summer Severe Weather Tool by adding another warm season and testing another statistical technique to determine if its performance can be improved. This task increases the period of record from 21 to 22 years and uses logistic regression to determine the appropriate predictors and provide a probability forecast. The performance of the logistic regression equations will be compared with the previous tool.

Accomplished: The severe weather database was updated with data from the 2010 warm season, increasing the period of record from 21 to 22 years. The verification statistics for the 2010 warm season Total Threat Scores (TTS) showed the tool did not perform well during that season. The data were stratified and predictor selection began for the statistical logistic regression analysis.



Tornado on KSC
Photo by anonymous USA employee

AMU ACCOMPLISHMENTS DURING THE PAST QUARTER

The progress being made in each task is provided in this section, organized by topic, with the primary AMU point of contact given at the end of the task discussion.

SHORT-TERM FORECAST IMPROVEMENT

Peak Wind Tool for User LCC, Phase IV (Ms. Crawford)

The peak winds are an important forecast element for the Expendable Launch Vehicle and Space Shuttle programs. As defined in the Launch Commit Criteria (LCC) and Shuttle Weather Flight Rules, each vehicle has peak wind thresholds that cannot be exceeded in order to ensure safe launch and landing operations. The 45th Weather Squadron (45 WS) and the Spaceflight Meteorology Group (SMG) indicate that peak winds are a challenging parameter to forecast, particularly in the cool season. To alleviate some of the difficulty in making this forecast, the AMU calculated cool season wind climatologies and peak speed probabilities for each of the towers used to evaluate LCC (Figure 1) in Phase I (Lambert 2002). In Phase III (Crawford 2010), the AMU updated these statistics with six more years of data, added a new time-period stratifications and created a graphical user interface (GUI) to display the desired values similar to that developed for SMG in Phase II (Lambert 2003). Based on recommendations from Phase III and observations by the launch weather officers (LWOs), the 45 WS tasked the AMU to stratify the data by stability and onshore/offshore flow and recalculate the climatologies and probabilities. These modifications will likely make the statistics more robust and useful to operations.

Data

The AMU archive contained most of the 5-minute wind tower and sounding data needed for this work,

but was missing data from the recent 3 years. Ms. Crawford collected these data from Mr. Madison of CSR. The data are from the cool season months October through April 1995–2010, resulting in 16 cool seasons in the period of record (POR). Ms. Crawford quality checked (QC'd) all tower and sounding data except for December 2010. Mr. Madison of CSR will deliver those data in January. She also determined that the hourly Shuttle Landing Facility (SLF) sea level pressure (SLP) data are needed to calculate the stability values for the stratification. She requested the values from the 14 WS, who will deliver the data in early January.

Stability Stratification

Ms. Crawford researched several stability parameters and discussed them with Dr. Merceret. They determined the gradient and bulk Richardson numbers (Ri and R_B ; Stull 1988) using tower and sounding data, respectively, will be used to determine the stability stratifications. The equation is similar for both:

$$Ri = \frac{\frac{g}{\Theta_v} \frac{\partial \Theta_v}{\partial z}}{\left[\left(\frac{\partial \bar{U}}{\partial z} \right)^2 + \left(\frac{\partial \bar{V}}{\partial z} \right)^2 \right]}$$

where g is gravity, z is height, Θ_v is the virtual potential tem-




Figure 1. Map showing the locations of the launch pads and LCC wind towers described in Table 1.

Table 1. Towers, and sensor heights that will be analyzed in this task with their associated launch vehicles.

Launch Vehicle	Tower(s)	Primary Height	Backup Height
Shuttle	393/394 (39A) 397/398 (39B)	60 ft	N/A
Atlas	41: primary 110: backup	230 ft 204 ft	54 ft
Delta II	2	90 ft	54 ft
Delta IV	6: primary 108: backup	54 ft	12 ft

perature, and U/V are the horizontal wind components. The horizontal bar over Θ_v , U, and V indicate a time-averaged value, in this case 5 minutes. For the towers, Ms. Crawford will calculate Ri at each level, and R_B will be calculated using data from the surface and boundary layer top levels in the soundings.

Ms. Crawford began creating the Θ_v values and u/v wind components needed to calculate Ri at the towers.

Virtual Potential Temperature

The tower data needed to calculate Θ_v are temperature (T) and dew point temperature (T_d). Ms. Crawford is using a standard set of thermodynamic equations to derive Θ_v from T and T_d . The first step is to calculate vapor pressure, e, using T_d (Rogers and Yau 1989):

$$e = 6.112 \exp \left[\frac{17.67(T_d)}{T_d + 243.5} \right]$$

Next, the mixing ratio, w is calculated using e and pressure (p):

$$w = \frac{0.622(e)}{p - e}$$

The potential temperature, Θ , is calculated using Poisson's Equation:

$$\Theta = T \left(\frac{1000 \text{ mb}}{p} \right)^{0.286}$$

This value and w are used to calculate Θ_v :

$$\Theta_v = \Theta [1 + 0.61(w)]$$

The wind towers do not have barometers to measure pressure, so the pressure at each level of the tower must be estimated. These pressures will be calculated using a derivation of the hydrostatic equation in which the lapse rate along the tower is constant (Hess 1959):

$$p = p_0 \left(\frac{T}{T_0} \right)^{\frac{g}{R\gamma}}$$

where p is the pressure at a tower level, p_0 is the surface pressure, T is the tower level temperature, T_0 is the surface temperature, g is gravity, R is the gas constant for dry air, and γ is the lapse rate. The hourly SLF sea level pressure will be p_0 and the 6-ft temperature will be T_0 .

Wind Components

The wind data are provided as speed in knots and direction in degrees. Ms. Crawford converted these

values to u and v components using

$$u = \text{spd} \times \cos \left[(270 - \text{dir}) \times \frac{\pi}{180} \right]$$

$$v = \text{spd} \times \sin \left[(270 - \text{dir}) \times \frac{\pi}{180} \right]$$

where spd is the speed in m/s and dir is the direction in degrees. Ms. Crawford converted the speed from knots to m/s with the relation

$$\text{spd} = \text{speed (kt)} \times 0.5175$$

Other Stratifications

Ms. Crawford will also stratify the data by month, hour, and onshore/offshore flow. In the previous phases, she stratified the data by direction in 10° sectors, and by hour and direction in 45° sectors. With the added stability and onshore/offshore stratifications it may not be possible to stratify by higher resolution direction sectors. As the data are processed and analyzed, Ms. Crawford will assess whether the data can support more directional stratifications.

Contact Ms. Crawford at crawford.winnie@ensco.com or 321-853-8130 for more information.

Situational Lightning Climatologies for Central Florida, Phase V (Dr. Bauman)

The threat of lightning is a daily concern during the warm season in Florida. Research has revealed distinct spatial and temporal distributions of lightning occurrence that are strongly influenced by large-scale atmospheric flow regimes. The 45 WS, SMG and National Weather Service in Melbourne, Fla. (NWS MLB) have the responsibility of issuing weather forecasts for airfields located in central Florida. SMG and 45 WS share forecasting responsibility for the SLF depending on the mission. The 45 WS has forecasting responsibility for the Cape Canaveral

Air Force Station (CCAFS) Skid Strip and Patrick Air Force Base (PAFB) while the NWS MLB is responsible for issuing terminal aerodrome forecasts (TAF) for airports throughout central Florida. In the previous phase (Bauman 2009), Dr. Bauman calculated lightning climatologies for the SLF and eight other airfields in central Florida based on a 19-year record of cloud-to-ground (CG) lightning data from the National Lightning Detection Network (NLDN) for the warm season months of May through September (1989-2007). The climatologies included the probability of lightning at 5-, 10-, 20- and 30-NM distances from the center point of the runway at each site. The climatologies were stratified by flow regimes with probabilities depicted at 1-, 3-, and 6-hr intervals. This phase up-

dates the previous work by adding 14 sites to the 9-site database including the CCAFS Skid Strip, PAFB and 12 commercial airports. It also adds three years of NLDN data resulting in a POR for the warm season months from 1989-2010. In addition to the flow regime stratification, moisture and stability stratifications will be added to separate more active from less active lighting days within the same flow regime.

Data Acquisition and Processing

Dr. Bauman requested the NLDN data for May-September 1989-2010 from Mr. Roeder of the 45 WS for the 23 sites. The 14 WS prepared the NLDN data files and Dr. Bauman downloaded them from their servers. He then processed the NLDN data using existing S-PLUS scripts to re-

move the cool season months from the data. He needed to create 2010 flow regime files and did so by first downloading NWS sounding data from the NOAA Earth System Research Laboratory for Jacksonville (JAX), Tampa (TBW), Miami (MFL) and CCAFS. Then he updated and tested S-PLUS scripts to create the warm season 2010 flow regime files and merged the flow regime data with the NLDN data.

Generate Lightning Climatologies

The goal of the first part of this task is to provide updated lightning climatologies using the longer POR and additional sites prior to the beginning of the 2011 warm season.

This does not include the additional stratifications by moisture or stability parameters. Dr. Bauman created S-PLUS scripts for the 14 additional sites to process the merged NLDN and flow regime data. These scripts separated the data into files containing NLDN data at 5-, 10-, 20- and 30-NM distances from the center point of the runway at each site at 1-, 3-, and 6-hr intervals stratified by flow regimes. He then generated the lightning climatologies for all 23 primary and backup sites for the 21-year period of record.

GUI Update

By more than doubling the number of sites in this phase of the work,

Dr. Bauman needed to find a more efficient way for the users to navigate through the stratifications in the GUI. He implemented a JavaScript drop-down menu for the GUI (Figure 2) that, at the top level, separates the sites by NWS forecast region and 45 WS/SMG sites. When the user rolls the mouse pointer over one of the menu items, subsequent drop-down menus are shown for the different stratifications allowing the user to choose the site, month or entire warm season and time interval or flow regime segregation. Dr. Bauman delivered the updated GUI to the customers for evaluation.




Figure 2. First page of the Hyper Text Markup Language (HTML)-based GUI shows a map of the sites color-coded by NWS forecast office region. The drop-down menu is located under the banner image at the top and depicts an example of a user choosing the PAFB site (COF) for August at 3-hr intervals.

New Stratifications

Dr. Bauman began incorporating the precipitable water (PWAT) observations from soundings at CCAFS, JAX, TBW and MFL into the sounding database. Ms. Crawford provided Dr. Bauman with code from existing S-PLUS scripts she wrote for other AMU tasks to first compute mixing ratio and then PWAT values. Ms. Crawford had previously calculated the PWAT values for the CCAFS soundings, so Dr. Bauman incorporated and modified the existing code to process the observations from the NWS sounding sites. He had to import the NWS sounding data from each of the three sites into S-PLUS, calculate mixing ratios and then PWAT for each warm season month, year and site.

After calculating the PWAT values, Dr. Bauman wrote scripts to verify the number of days and their associated PWAT values were correct. He manually spot-checked the data for several sites against the verifica-

tion scripts for the entire warm season and then for each warm season month. Once he knew the calculations were correct, he began generating new lightning climatologies for all of the sites using the PWAT stratification.

Table 2 shows the PWAT stratification from the CCAFS sounding data for the warm season months. The PWAT values for the JAX, TBW and MFL soundings are not shown. The values were derived from precipitable water plots created by Mr. Matthew Bunkers, the Science and Operations Officer at the Rapid City, S.D. NWS Forecast Office (<http://www.crh.noaa.gov/unr/?n=pw>). Based on discussions with Mr. Sharp at NWS MLB, values below the 25th

Table 2. The PWAT stratification thresholds for the warm season months from the CCAFS sounding data from 1950-2009. The low values represent the 25th percentile and the high values the 75th percentile from the dataset with the medium values falling between the two.

Month	Low	Medium	High
May	< 1.00"	1.01" to 1.49"	> 1.50"
June	< 1.45"	1.46" to 1.89"	> 1.90"
July	< 1.60"	1.61" to 1.94"	> 1.95"
August	< 1.65"	1.66" to 2.04"	> 2.05"
September	< 1.55"	1.56" to 1.99"	> 2.00"

percentile will be considered low, values above the 75th percentile will be considered high, and the values between them and inclusive will be considered medium.

For more information contact Dr. Bauman at 321-853-8202 or bauman.bill@ensco.com.

Vandenberg Air Force Base North Base Wind Study (Mr. Wheeler)

The 30 WS states that terrain influences along the extreme northern fringes of Vandenberg Air Force Base (VAFB) make it difficult for forecasters to issue timely and accurate high wind warnings for that particular part of the base during northeasterly wind events. These events tend to occur during the winter or early spring when they are under the influence of the Great Basin high pressure weather regime. The LWOs have seen these rapid wind increases in the current Towers 60, 70 and 71 along the northern edge of VAFB in excess of the 35 kt warning threshold. For this task, the 30 WS requested the AMU analyze data from days when these towers reported winds in excess of 35 kt and determine if there are any precursors in the observations that would allow the LWOs to better forecast and warn their operational customers for these wind events.

VAFB Wind Tower Database

Figure 3 is a Google Earth map showing the locations of the wind towers on VAFB. Towers 60, 70 and 71 along the northern part of VAFB are the primary wind towers Mr. Wheeler will use for this study.

Mr. Wheeler requested the VAFB weather data prior to September 2010, but due to a heavy workload and an Operational Readiness Inspection at the 30 WS, he received the tower data in mid-October on several compact discs (CDs). He also received a list of the suspected 35-kt wind event days from 2004 through the spring of 2010. The wind tower data from 2004 to October 2007 was from the legacy mechanical wind sensors and the data from November 2007 through March 2010 was from the ultrasonic sensors. The legacy wind data were obtained from a cup-and-vane system with the vane (direction) and cups (speed) mounted separately, but at the same level. The ultrasonic sensor derives wind speed and direction from the



Figure 3. Google Earth map of the VAFB tower locations as yellow circles with white tower numbers. The towers for this task are surrounded by the yellow ellipse.

effect of wind on the transit time of ultrasonic pulses between three electro-acoustic transducers configured in an equilateral triangle.

Mr. Wheeler copied the wind tower data files from the CDs and moved them to yearly and monthly folders. The tower data files were compressed, so he had to uncompress and extract the monthly and daily data. He then ran Excel scripts

developed by Dr. Bauman to extract the the 6, 12 and 54 foot wind direction and speed along with temperature and humidity from the data files. Mr. Wheeler used several computers to do this extraction process as the data from 2007 through 2010 was in 1-minute Network Common Data Form (NetCDF) format and took a long time to extract each day's data set. While this was being done he retrieved surface, 500 and 850 mb

upper air weather maps of the Southwest US on another computer, and also retrieved VAFB sounding data for each of the event days from Plymouth State University and the National Centers for Environmental Prediction weather data archives.

For more information contact Mr. Wheeler at 321-853-8205 or wheeler.mark@ensco.com.

INSTRUMENTATION AND MEASUREMENT

Upgrade Summer Severe Weather Tool Phase III (Dr. Watson)

The 45 WS Commander's morning weather briefing includes an assessment of the likelihood of local convective severe weather for the day. This forecast is provided in order to enhance protection of personnel and material assets of the 45th Space Wing, CCAFS, and KSC. The severe weather elements produced by thunderstorms include tornadoes, convective surface winds of 50 knots, and/or hail with a diameter of 0.75 inches. Forecasting the occurrence and timing of these phenomena during the warm season (May – September) is challenging for 45 WS operational personnel. In previous tasks, the AMU analyzed stability parameters and synoptic patterns from Central Florida severe weather days during 1989-2003 to determine which were important to severe weather development (Bauman et al. 2005). The AMU then created an HTML-based tool using the important parameters and patterns to help de-

termine the probability of issuing severe weather watches and warnings for the day. The HTML tool was replaced with a Meteorological Interactive Data Display System (MIDDS)-based GUI in a follow-on task (Wheeler 2009) that retrieved stability parameters and other information from MIDDS automatically, minimizing the forecaster's interaction with the tool. Later, the AMU updated the severe weather database with data from the years 2004-2009, re-analyzed the data to determine the important parameters, made appropriate adjustments to the index weights depending on the results of the analysis, and updated the MIDDS GUI (Wheeler 2010). For this task, the 45 WS requested the AMU upgrade the severe weather database by adding weather observations from 2010, update the verification data set with results from the summer of 2010, use statistical logistic regression analysis on the database and develop a new forecast tool if appropriate, and update the MIDDS GUI, if necessary.

Severe Weather Database

Dr. Watson retrieved the May – September 2010 severe weather reports from the Storm Prediction Center and the National Climatic Data Center databases and integrated the reports into the existing severe weather database. She included stability indices calculated from the local rawindsondes as well as the Florida large-scale flow regime data provided by Ms. Crawford. She also used archived upper air data from Plymouth State University to plot and analyze the jet stream characteristics over Florida. Inclusion of these data increases the period of record from 21 to 22 years (1989 – 2010).

2010 Verification Results

Dr. Watson computed verification statistics for the 2010 warm season using the Total Threat Score (TTS) computed from the MIDDS GUI (Table 3). The AMU and 45 WS forecasters computed the TTS for 132 days during May – September 2010 with values ranging from -23 to 20. Severe weather was reported in east-central Florida on 15 days during the warm season. The TTS forecast threshold value for computing the statistics was 5: if < 5 it was a No forecast and if ≥ 5 it was a Yes forecast. If severe weather was reported across these Florida counties, that was classified as an observed Yes. The Severe Weather Worksheet TTS did not verify well in the 2010 warm season, with a high False Alarm Rate

Table 3. Warm season 2010 TTS Verification Statistics		Observed Severe		FAR = 0.54
		Yes	No	
Forecast Severe	Yes	6	7	POD = 0.43
	No	8	111	CSI = 0.29
				HSS = 0.37
				TSS = 0.37

(FAR) and low values for Probability of Detection (POD), Critical Success Index (CSI), Heidke Skill Score (HSS), and True Skill Statistic (TSS) (Wheeler 2010).

Logistic Regression Analysis

Dr. Watson installed and began learning the S-PLUS statistical software that is used to perform the statistical logistic regression analysis. She stratified the data into equation development and verification datasets. The development dataset re-

quires enough samples so that the resulting set of equations is stable. Therefore, data from 1989 to 2008 were chosen as the development dataset. This dataset included 380 severe weather days out of 2742 total days.

She began predictor selection using the development dataset and the procedure outlined in Lambert and Wheeler (2005). The predictand is 0 or 1 depending on whether severe weather occurred (1) or not (0). The eight candidate predictors in-

cluded the

- Total Totals,
- K-Index,
- Lifted Index,
- Thompson Index,
- Showalter Stability Index,
- Precipitable Water,
- Flow Regime, and
- Jet stream characteristics.

For more information contact Dr. Watson at 321-853-8264 or watson.leela@ensco.com.

REFERENCES

- Bauman, W., M. Wheeler and D. Short, 2005: Severe Weather Forecast Decision Aid. NASA Contractor Report CR-2005-212563, Kennedy Space Center, FL, 50 pp. [Available from ENSCO, Inc., 1980 N. Atlantic Ave., Suite 830, Cocoa Beach, FL, 32931 and online at <http://science.ksc.nasa.gov/amu/finalreports/severe-tool-final.pdf>.]
- Bauman, W. H. III, 2009: Situational Lightning Climatologies for Central Florida: Phase IV. NASA Contractor Report CR-2009-214763, Kennedy Space Center, FL, 39 pp. [Available from ENSCO, Inc., 1980 N. Atlantic Ave., Suite 830, Cocoa Beach, FL 32931 and <http://science.ksc.nasa.gov/amu/final-reports/lightning-climo-phase4.pdf>.]
- Crawford, W., 2010: Statistical Short-Range Guidance for Peak Wind Forecasts on Kennedy Space Center/Cape Canaveral Air Force Station, Phase III. NASA Contractor Report CR-2010-216281, Kennedy Space Center, FL, 33 pp. [Available from ENSCO, Inc., 1980 N. Atlantic Ave., Suite 830, Cocoa Beach, FL 32931 and <http://science.ksc.nasa.gov/amu/final-reports/windstats-phase3.pdf>.]
- Hess, S. L., 1959: *Introduction to Theoretical Meteorology*. Robert E. Krieger Publishing Company, Malabar, FL, 364 pp.
- Lambert, W., 2002: Statistical Short-Range Guidance for Peak Wind Speed Forecasts on Kennedy Space Center/Cape Canaveral Air Force Station: Phase I Results. NASA Contractor Report CR-2002-211180, Kennedy Space Center, FL, 39 pp. [Available from ENSCO, Inc., 1980 N. Atlantic Ave., Suite 830, Cocoa Beach, FL 32931 and <http://science.ksc.nasa.gov/amu/final-reports/windstats-phase1.pdf>.]
- Lambert, W., 2003: Extended Statistical Short-Range Guidance for Peak Wind Speed Analyses at the Shuttle Landing Facility: Phase II Results. NASA Contractor Report CR-2003-211188, Kennedy Space Center, FL, 27 pp. [Available from ENSCO, Inc., 1980 N. Atlantic Ave., Suite 830, Cocoa Beach, FL 32931 and <http://science.ksc.nasa.gov/amu/final-reports/windstats-phase2.pdf>.]
- Lambert, W. and M. Wheeler, 2005: Objective lightning probability forecasting for Kennedy Space Center and Cape Canaveral Air Force Station. NASA Contractor Report CR-2005-212564, Kennedy Space Center, FL, 54 pp. [Available from ENSCO, Inc., 1980 N. Atlantic Ave., Suite 830, Cocoa Beach, FL, 32931, and online at <http://science.ksc.nasa.gov/amu/final-reports/objective-ltg-fcst-phase1.pdf>.]
- Willett, J. C. and F. J. Merceret, E. P. Krider, J. E. Dye, T. P. O'Brien, W. D. Rust, R. L. Walterscheid, J. T. Madura, and H. J. Christian, 2010: *Rationales for the Lightning Flight Commit Criteria*, NASA/TP-2010-216291, 248 pp.
- Rogers, R. R. and M. K. Yau, 1989: *A Short Course in Cloud Physics*. Pergamon Press, New York, NY, 293 pp.
- Stull, R. B., 1988: *An Introduction to Boundary Layer Meteorology*. Kluwer Academic Publishers, Dordrecht, The Netherlands, 670 pp.
- Wheeler, M., 2009: Severe Weather and Weak Waterspout Checklist in MIDDs. NASA Contractor Report CR-2009-214760, Kennedy Space Center, FL, 16 pp. [Available from ENSCO, Inc., 1980 N. Atlantic Ave., Suite 830, Cocoa Beach, FL, 32931 and online at <http://science.ksc.nasa.gov/amu/final-reports/svr-wx-wkshtmiddles.pdf>.]
- Wheeler, M., 2010: Upgrade Summer Severe Weather Tool in MIDDs. NASA Contractor Report CR-2010-216282, Kennedy Space Center, FL, 15 pp. [Available from ENSCO, Inc., 1980 N. Atlantic Ave., Suite 830, Cocoa Beach, FL, 32931 and online at <http://science.ksc.nasa.gov/amu/final-reports/severe-tool-upgrade.pdf>.]

AMU ACTIVITIES

AMU Chief's Technical Activities (Dr. Merceret)

Dr. Merceret completed final processing of the Lightning Launch Commit Criteria Rationale for formal public release (Merceret and Willett, 2010). The document will be available after 10 January 2011.

Dr. Merceret contributed as a co-author with Dr. Lisa Huddleston and Mr. Roeder on a paper to be submitted to the Journal of Atmospheric and Oceanic Technology describing a new methodology for using CGLSS and NLDN data to assess the probability that lightning struck within a defined distance of a specified target, such as LC39. He also prepared an extended abstract about the

AMU to be presented at the 91st Annual Meeting of the American Meteorological Society (AMS) in January. After it was reviewed by his co-authors John Madura, Bill Bauman, Bill Roeder, Frank Brody and Bart Hagemeyer, he submitted the document to the AMS. Dr. Bauman, Dr. Merceret and Mr. Roeder developed a PowerPoint presentation for review by the other co-authors.

AMU OPERATIONS (AMU Team)

Launch Support

Dr. Watson supported the Delta 4-Heavy launch on 21 November. Ms. Wilson and Mr. Wheeler supported the Falcon 9 launch on 8 December.

LIST OF ACRONYMS

14 WS	14th Weather Squadron	LCC	Launch Commit Criteria
30 SW	30th Space Wing	LWO	Launch Weather Officer
30 WS	30th Weather Squadron	MFL	Miami, Fla. 3-letter identifier
45 RMS	45th Range Management Squadron	MIDDS	Meteorological Interactive Data Display System
45 OG	45th Operations Group	MSFC	Marshall Space Flight Center
45 SW	45th Space Wing	NLDN	National Lightning Detection Network
45 SW/SE	45th Space Wing/Range Safety	NOAA	National Oceanic and Atmospheric Administration
45 WS	45th Weather Squadron	NWS MLB	National Weather Service in Melbourne, FL
AFSPC	Air Force Space Command	PAFB	Patrick Air Force Base
AFWA	Air Force Weather Agency	POD	Probability of Detection
AMU	Applied Meteorology Unit	POR	Period of Record
CCAFS	Cape Canaveral Air Force Station	PWAT	Precipitable Water
CD	Compact Disc	QC	Quality Control
CG	Cloud-to-Ground lightning	SLF	Shuttle Landing Facility
CSI	Critical Success Index	SLP	Sea Level Pressure
CSR	Computer Sciences Raytheon	SMC	Space and Missile Center
FAR	False Alarm Rate	SMG	Spaceflight Meteorology Group
FSU	Florida State University	TAF	Terminal Aerodrome Forecast
FY	Fiscal Year	TBW	Tampa, Fla. 3-letter identifier
GSD	Global Systems Division	TSS	True Skill Statistic
GUI	Graphical User Interface	TTS	Total Threat Score
HSS	Heidke Skill Score	USAF	United States Air Force
HTML	Hyper Text Markup Language	VAFB	Vandenberg Air Force Base
JAX	Jacksonville, Fla. 3-letter identifier		
JSC	Johnson Space Center		
KSC	Kennedy Space Center		

The AMU has been in operation since September 1991. Tasking is determined annually with reviews at least semi-annually.

AMU Quarterly Reports are available on the Internet at <http://science.ksc.nasa.gov/amu/>.

They are also available in electronic format via email. If you would like to be added to the email distribution list, please contact Ms. Winifred Crawford (321-853-8130, crawford.winnie@ensco.com).

If your mailing information changes or if you would like to be removed from the distribution list, please notify Ms. Crawford or Dr. Francis Merceret (321-867-0818, Francis.J.Merceret@nasa.gov).

Distribution

NASA HQ/M/AA/ W. Gerstenmaier	45 WS ADO/W. Whisel	HQ USAF/Integration, Plans, and Requirements Div/ Directorate of Weather/ A30-WX	412 OSS/OSWM/C. Donohue
NASA KSC/AA/R. Cabana	45 WS/DOR/M. McAleenan		UAH/NSSTC/W. Vaughan
NASA KSC/MK/L. Cain	45 WS/DOR/M. Buchanan		FAA/K. Shelton-Mur
NASA KSC/LX/P. Phillips	45 WS/DOR/K. Josephson	NOAA "W/NP"/L. Uccellini	FSU Department of Meteorology/H. Fuelberg
NASA KSC/PH/ R. Willcoxon	45 WS/DOR/R. Parker	NOAA/OAR/SSMC-I/J. Golden	ERAU/Applied Aviation Sciences/C. Herbst
NASA KSC/PH-A2/D. Lyons	45 WS/DOR/F. Flinn	NOAA/NWS/OST12/SSMC2/ J. McQueen	ERAU/J. Lanicci
NASA KSC/PH/M. Leinbach	45 WS/DOR/ T. McNamara	NOAA Office of Military Affairs/ M. Babcock	NCAR/J. Wilson
NASA KSC/PH/S. Minute	45 WS/DOR/J. Tumbiolo		NCAR/Y. H. Kuo
NASA KSC/VA/A. Mitskevich	45 WS/DOR/K. Winters	NWS Melbourne/B. Hagemeyer	NOAA/FRB/GSD/J. McGinley
NASA KSC/VA-2/C. Dovale	45 WS/DOR/D. Craft	NWS Melbourne/D. Sharp	Office of the Federal Coordinator for Meteorological Services and Supporting Research/ R. Dumont
NASA KSC/KT-C/J. Perotti	45 WS/SYA/J. Saul	NWS Melbourne/S. Spratt	
NASA KSC/PH-3/J. Madura	45 WS/SYR/W. Roeder	NWS Melbourne/P. Blottman	Boeing Houston/S. Gonzalez
NASA KSC/PH-3/F. Merceret	45 RMS/CC/T. Rock	NWS Melbourne/M. Volkmer	Aerospace Corp/T. Adang
NASA KSC/PH-3/J. Wilson	45 SW/CD/G. Kraver	NWS Southern Region HQ/"W/ SR"/S. Cooper	ITT/G. Kennedy
NASA KSC/NEM50/ L. Huddleston	45 SW/SELR/K. Womble	NWS Southern Region HQ/"W/ SR3"/D. Billingsley	Timothy Wilfong & Associates./ T. Wilfong
NASA JSC/WS8/F. Brody	45 SW/XPR/R. Hillyer	NWS/"W/OST1"/B. Saffle	ENSCO, Inc./J. Clift
NASA JSC/WS8/B. Hoeth	45 OG/CC/J. Ross	NWS/"W/OST12"/D. Melendez	ENSCO, Inc./E. Lambert
NASA JSC/WS8/ K. Van SpeyBroeck	CSR 4500/J. Osier	NWS/OST/PPD/SPB/P. Roehr	ENSCO, Inc./A. Yersavich
NASA MSFC/EV44/D. Edwards	CSR 4500/T. Long	NSSL/D. Forsyth	ENSCO, Inc./S. Masters
NASA MSFC/EV44/B. Roberts	CSR 7000/M. Maier	30 WS/DO/J. Roberts	
NASA MSFC/EV44/R. Decker	SMC/RNP/M. Erdmann	30 WS/DOR/D. Vorhees	
NASA MSFC/EV44/H. Justh	SMC/RNP/T. Nguyen	30 WS/SY/M. Schmeiser	
NASA MSFC/MP71/G. Overbey	SMC/RNP/R. Bailey	30 WS/SYR/G. Davis	
NASA MSFC/SPoRT/ G. Jedlovec	SMC/RNP(PRC)/K. Spencer	30 SW/XPE/R. Ruecker	
NASA DFRC/RA/E. Teets	HQ AFSPC/A3FW/J. Carson	Det 3 AFWA/WXL/K. Lehneis	
NASA LaRC/M. Kavaya	HQ AFWA/A3/5/M. Surmeier	NASIC/FCTT/G. Marx	
45 WS/CC/E. Borelli	HQ AFWA/A8TP/G. Brooks	46 WS//DO/J. Mackey	
45 WS/DO/L. Shoemaker	HQ AFWA/A5R/M. Gremillion	46 WS/WST/E. Harris	
	HQ USAF/A30-W/R. Stoffer	412 OSS/OSW/P. Harvey	
	HQ USAF/A30-WX/ M. Zettlemoyer		



NOTICE: Mention of a copyrighted, trademarked, or proprietary product, service, or document does not constitute endorsement thereof by the author, ENSCO, Inc., the AMU, the National Aeronautics and Space Administration, or the United States Government. Any such mention is solely for the purpose of fully informing the reader of the resources used to conduct the work reported herein.